

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26

Version: 7.0

Page: 1/9

(30507854/SDS_CPA_US/EN)

1. Product and Company Identification

Company

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Substance number: 000000458813

2. Hazards Identification

Emergency overview

CAUTION:
EXTREMELY FLAMMABLE.
KEEP OUT OF REACH OF CHILDREN.
KEEP OUT OF REACH OF DOMESTIC ANIMALS.
HARMFUL IF SWALLOWED.
HARMFUL IF ABSORBED THROUGH SKIN.
Avoid contact with the skin, eyes and clothing.
Wash thoroughly after handling.
Aerosol container contains flammable gas under pressure.

See Product Label for additional precautionary statements.

State of matter: liquid
Colour: amber, cloudy
Odour: characteristic, of acetone

Potential health effects**Primary routes of exposure:**

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Slightly toxic after single ingestion. Slightly toxic after short-term skin contact. Relatively nontoxic after short-term inhalation.

Irritation / corrosion:

May cause slight but temporary irritation to the eyes. May cause slight irritation to the skin.

Sensitization:

Skin sensitizing effects were not observed in animal studies.

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26
Version: 7.0

Page: 2/9
(30507854/SDS_CPA_US/EN)

Signs and symptoms of overexposure:

Vomiting may cause aspiration pneumonia due to the ingredients.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
8003-34-7	0.5 %	Pyrethrins
51-03-6	1.0 %	Piperonylbutoxide
115-10-6		dimethyl ether
124-38-9		carbon dioxide
64742-47-8		Distillates (petroleum), hydrotreated light
67-64-1	>= 55.0 %	Acetone
	<= 45.0 %	Proprietary ingredients

4. First-Aid Measures

General advice:

First aid providers should wear personal protective equipment to prevent exposure. Remove contaminated clothing. Move person to fresh air. If person is not breathing, call 911 or ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or physician for treatment advice. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

If inhaled:

Remove the affected individual into fresh air and keep the person calm.

If on skin:

Rinse skin immediately with plenty of water for 15 - 20 minutes.

If in eyes:

Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.

If swallowed:

Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not give solids or liquids.

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote. Aspiration of this product during induced emesis can result in lung injury. If evacuation of stomach contents is considered necessary, use method least likely to cause aspiration, such as gastric lavage after endotracheal intubation.

5. Fire-Fighting Measures

Lower explosion limit:

As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.

Upper explosion limit:

As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.

Flammability of Aerosol Products: > 18 in

(ASTM D 3065)

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26
Version: 7.0

Page: 3/9
(30507854/SDS_CPA_US/EN)

NFPA 30B flammability:
Level 2 Aerosol

Suitable extinguishing media:
carbon dioxide, foam, dry powder, water spray

Hazards during fire-fighting:
carbon monoxide, carbon dioxide, nitrogen dioxide, nitrogen oxide,
Aerosol container contains flammable gas under pressure. Pressure inside container is increased when heated, and may cause explosion. If product is heated above decomposition temperature, toxic vapours will be released. The substances/groups of substances mentioned can be released in case of fire.

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:
Evacuate area of all unnecessary personnel. Contain contaminated water/firefighting water. Do not allow to enter drains or waterways.

6. Accidental release measures

Personal precautions:
Take appropriate protective measures. Clear area. Shut off source of leak only under safe conditions. Extinguish sources of ignition nearby and downwind. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Environmental precautions:
Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water. A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities. This product is regulated by CERCLA ('Superfund').

Cleanup:
Dike spillage. Pick up with suitable absorbent material. Spilled substance/product should be recovered and applied according to label rates whenever possible. If application of spilled substance/product is not possible, then spills should be contained, solidified, and placed in suitable containers for disposal. After decontamination, spill area can be washed with water. Collect wash water for approved disposal.

7. Handling and Storage

Handling

General advice:
RECOMMENDATIONS ARE FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS. PESTICIDE APPLICATORS & WORKERS must refer to the Product Label and Directions for Use attached to the product. Provide good ventilation of working area (local exhaust ventilation if necessary). Keep away from sources of ignition - No smoking. Keep container tightly sealed. Protect against heat. Handle and open container with care. Do not open until ready to use. Once container is opened, content should be used as soon as possible. Provide means for controlling leaks and spills. Follow label warnings even after container is emptied. The substance/ product may be handled only by appropriately trained personnel. Avoid all direct contact with the substance/product. Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts/mists/vapours. Wear suitable personal protective clothing and equipment.

Protection against fire and explosion:
Aerosol container contains flammable gas under pressure. The relevant fire protection measures should be noted. Fire extinguishers should be kept handy. Avoid all sources of ignition: heat, sparks, open flame. Avoid extreme heat. Ground all transfer equipment properly to prevent electrostatic discharge. Electrostatic discharge may cause ignition.

Storage

General advice:

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26

Page: 4/9

Version: 7.0

(30507854/SDS_CPA_US/EN)

Protect containers from physical damage. Store in a cool, dry, well-ventilated area. Avoid all sources of ignition: heat, sparks, open flame.

Storage incompatibility:

General advice: Segregate from incompatible substances. Segregate from foods and animal feeds. Segregate from textiles and similar materials.

Storage stability:

May be kept indefinitely if stored properly. If an expiry date is mentioned on the packaging/label this takes priority over the statements on storage duration in this safety data sheet.

Temperature tolerance

Protect from temperatures above: 130 °F
Explosive at or above indicated temperature.

8. Exposure Controls and Personal Protection

Users of a pesticidal product should refer to the product label for personal protective equipment requirements.

Components with occupational exposure limits

Pyrethrins	OSHA PEL	PEL 5 mg/m ³ ;
	ACGIH TLV	TWA value 5 mg/m ³ ;
Acetone	OSHA PEL	PEL 1,000 ppm 2,400 mg/m ³ ;
	ACGIH TLV	TWA value 500 ppm ; STEL value 750 ppm ;
carbon dioxide	OSHA PEL	PEL 5,000 ppm 9,000 mg/m ³ ;
Distillates (petroleum), hydrotreated light	ACGIH TLV	TWA value 200 mg/m ³ Non-aerosol (total hydrocarbon vapor); Application restricted to conditions in which there are negligible aerosol exposures. Skin Designation Non-aerosol (total hydrocarbon vapor); The substance can be absorbed through the skin.

Advice on system design:

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment.

Personal protective equipment

RECOMMENDATIONS FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS:

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator. For situations where the airborne concentrations may exceed the level for which an air purifying respirator is effective, or where the levels are unknown or Immediately Dangerous to Life or Health (IDLH), use NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection:

Chemical resistant protective gloves, Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26
Version: 7.0

Page: 5/9
(30507854/SDS_CPA_US/EN)

General safety and hygiene measures:

RECOMMENDATIONS FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS

Wear long sleeved work shirt and long work pants in addition to other stated personal protective equipment. Work place should be equipped with a shower and an eye wash. Handle in accordance with good industrial hygiene and safety practice. Personal protective equipment should be decontaminated prior to reuse. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Take off immediately all contaminated clothing. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift. No eating, drinking, smoking or tobacco use at the place of work. Keep away from food, drink and animal feeding stuffs.

9. Physical and Chemical Properties

Form:	liquid, aerosol	
Odour:	characteristic, of acetone	
Colour:	amber, cloudy	
pH value:	8.7	(23.4 °C)
Density:	0.859 g/cm3	(20 °C)
Vapour density:		not determined
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Viscosity, dynamic:	0.99 cps	(20 °C)
Solubility in water:		slightly soluble

10. Stability and Reactivity

Conditions to avoid:

Avoid all sources of ignition: heat, sparks, open flame. Avoid prolonged storage. Avoid electro-static discharge. Avoid contamination. Avoid prolonged exposure to extreme heat. Avoid extreme temperatures.

Substances to avoid:

No substances known that should be avoided.

Hazardous reactions:

The product is chemically stable.

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

Possible thermal decomposition products:

carbon monoxide, carbon dioxide, nitrogen dioxide, nitrogen oxide

Stable at ambient temperature. If product is heated above decomposition temperature toxic vapours may be released. To avoid thermal decomposition, do not overheat.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

11. Toxicological information

Acute toxicity

Oral:

Type of value: LD50

Species: rat

Value: > 2,000 mg/kg

Inhalation:

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26
Version: 7.0

Page: 6/9
(30507854/SDS_CPA_US/EN)

Type of value: LC50
Species: rat
Value: > 7.4 mg/l

Dermal:

Type of value: LD50
Species: rat
Value: > 2,000 mg/kg

Irritation / corrosion

Skin:

Species: rabbit
Result: non-irritant
May cause slight irritation to the skin.

Eye:

Species: rabbit
Result: mildly irritating
May cause slight irritation to the eyes.

Sensitization:

Species: guinea pig
Result: Non-sensitizing.

Genetic toxicity

Information on: pyrethrum
No mutagenic effects reported.

Information on: Piperonyl butoxide
Mutagenicity tests revealed no genotoxic potential.

Information on: dimethyl ether
No mutagenic effect was found in various tests with microorganisms and mammalian cell culture. Literature data.

Carcinogenicity

Information on: pyrethrum
Not Likely to Be Carcinogenic to Humans.

Information on: Piperonyl butoxide
In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. The US EPA has classified this substance with the rating of 'C', possible human carcinogen.

Reproductive toxicity

Information on: pyrethrum
No reproductive toxic effects reported.

Information on: Piperonyl butoxide
No reproductive toxic effects reported.

The results of animal studies gave no indication of a fertility impairing effect.

Information on: dimethyl ether

The results of animal studies gave no indication of a fertility impairing effect. Literature data.

Development:

Information on: pyrethrum

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26
Version: 7.0

Page: 7/9
(30507854/SDS_CPA_US/EN)

Information on: Piperonyl butoxide
No indications of a developmental toxic / teratogenic effect were seen in animal studies.
Information on: dimethyl ether
In animal studies the substance did not cause malformations. Literature data.

Other Information:

Misuse can be harmful to health.

12. Ecological Information

Fish

Acute:
Oncorhynchus mykiss/LC50 (96 h):

Information on: pyrethrum
Acute:
static
Oncorhynchus mykiss/LC50 (96 h): 0.0052 mg/l
Lepomis macrochirus/LC50 (96 h): 0.01 mg/l

Information on: Piperonyl butoxide
Acute:
other Oncorhynchus mykiss/LC50 (96 h): 6.12 mg/l

Information on: dimethyl ether
Acute:
other semistatic
Poecilia reticulata/NOEC (96 h): > 4,000 mg/l
The product is highly volatile. Tested in a closed test system.

Aquatic invertebrates

Information on: Piperonyl butoxide
Acute:
other Daphnia magna/EC50 (48 h): 0.51 mg/l

Information on: dimethyl ether
Acute:
other static
Daphnia magna/No observed effect concentration (48 h): > 4,000 mg/l
The product is highly volatile. Tested in a closed test system.

13. Disposal considerations

Waste disposal of substance:

Pesticide wastes are regulated. Improper disposal of excess pesticide, spray mix or rinsate is a violation of federal law. If pesticide wastes cannot be disposed of according to label instructions, contact the State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container disposal:

Do not cut, puncture, crush, or incinerate empty aerosol containers. Consult state or local disposal authorities for approved alternative procedures such as container recycling. Empty aerosol cans may meet the definition of RCRA D003. Consult local and/or regional EPA for further guidance.

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26
Version: 7.0

Page: 8/9
(30507854/SDS_CPA_US/EN)

14. Transport Information

Land transport

USDOT

Hazard class: 2.1
ID number: UN 1950
Hazard label: 2.1
Proper shipping name: AEROSOLS (contains DIMETHYLETHER)

Sea transport

IMDG

Hazard class: 2.1
ID number: UN 1950
Hazard label: 2.1
Marine pollutant: NO
Proper shipping name: AEROSOLS (contains DIMETHYLETHER)

Air transport

IATA/ICAO

Hazard class: 2.1
ID number: UN 1950
Hazard label: 2.1
Proper shipping name: AEROSOLS, FLAMMABLE (contains DIMETHYLETHER)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US blocked / not listed

Crop Protection TSCA, US released / exempt

OSHA hazard category: Chronic target organ effects reported; ACGIH TLV established

EPCRA 311/312 (Hazard categories): Acute; Chronic

EPCRA 313:

<u>CAS Number</u>	<u>Chemical name</u>
51-03-6	Piperonylbutoxide

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	67-64-1	Acetone
100 LBS	115-10-6	dimethyl ether
1 LBS	8003-34-7	Pyrethrins

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	8003-34-7	Pyrethrins
NJ	51-03-6	Piperonylbutoxide

Safety Data Sheet

PT 565 PLUS XLO FORMULA 2

Revision date : 2013/12/26

Page: 9/9

Version: 7.0

(30507854/SDS_CPA_US/EN)

MA, NJ, PA	115-10-6	dimethyl ether
MA, NJ, PA	124-38-9	carbon dioxide
MA, NJ, PA	64742-47-8	Distillates (petroleum), hydrotreated light

16. Other Information

Refer to product label for EPA registration number.

Recommended use: insecticide

NFPA Hazard codes:

Health : 1 Fire: 3 Reactivity: 1 Special:

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

SDS Prepared by:

BASF NA Product Regulations

msds@basf.com

SDS Prepared on: 2013/12/26

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET